



SERIE 032 ■

PNEUMATIC COUPLINGS
PNEUMATISCHE KUPPLUNGEN



Interchangeability - Kompatibilität
RECTUS 32KA, TEMA 1800

Temperature Range - Temperaturbereich
-20°C +100°C (-4°F +212°F)

Working Pressure - Betriebsdruck
0 - 35 bar (0 - 508 PSI)

Flow capacity - Nennweite
NW - 10



Options - Optionen

- F - Straight through flow - ungehinterter Durchfluss
- S - Stainless Steel - Edelstahl
- V - FPM Seal - FKM Dichtung
- E - EPDM Seal - EPDM Dichtung

For optional orders please add the symbol of your option end of the order no.
Bei Optionsbestellungen Kennbuchstabe bitte hinzufügen (Beispiel: 032 RG 13-K-V)

Material - Material

- Coupler Body - Kupplungsgrundkörper: Brass Nickel Plated - Messing vernickelt
- Back Part - Hinterteil: Brass Nickel Plated - Messing vernickelt
- Sleeve - Hülse: Steel Nickel Plated - Stahl vernickelt
- Valve - Ventil: Messing Diecasting
- Springs - Federn: Stainless Steel - Edelstahl
- Balls - Kugeln: Stainless Steel - Edelstahl AISI 420
- Seals - Dichtungen: Nitrile (Ni) - NBR (Ni)
- Plug - Nippel: Steel Nickel Plated - Stahl vernickelt



Couplers and Plugs
Kupplungen und Nippel


Connection
Anschlüsse

Order No
Bestellnr.


SW

L


ØD




Male Threaded Coupling
Kupplung mit Aussengewinde




Female Thread Coupling
Kupplung mit Innengewinde



Standard Hose Barb Coupling
Kupplung mit Schlauchtülle



Standard Hose Barb Plug
Nippel mit Schlauchtülle



Male Threaded Plug
Nippel mit Aussengewinde



Female Thread Plug
Nippel mit Innengewinde

BSPT 1/4"	032 RG 13	24	65	28
BSPT 3/8"	032 RG 17	24	65	28
BSPT 1/2"	032 RG 21	24	65	28
BSPT 3/4"	032 RG 26	27	65	28

BSP 1/4"	032 DG 13	24	59	28
BSP 3/8"	032 DG 17	24	59	28
BSP 1/2"	032 DG 21	24	62	28

8 mm - 5/16"	032 HG 08	24	75	28
10 mm - 3/8"	032 HG 10	24	75	28
13 mm - 1/2"	032 HG 13	24	75	28
16 mm - 5/8"	032 HG 16	24	75	28
19 mm - 3/4"	032 HG 19	24	75	28


6 mm - 1/4"	032 HU 06		48	
8 mm - 5/16"	032 HU 08		48	
9 mm - 5/14"	032 HU 09		48	
10 mm - 3/8"	032 HU 10		48	
13 mm - 1/2"	032 HU 13		48	
16 mm - 5/8"	032 HU 16		48	
19 mm - 3/4"	032 HU 19		48	

BSPT 1/4"	032 RU 13	16	39	
BSPT 3/8"	032 RU 17	17	39	
BSPT 1/2"	032 RU 21	22	42	
BSPT 3/4"	032 RU 26	27	44	

BSP 1/4"	032 DU 13	16	36	
BSP 3/8"	032 DU 17	20	36	
BSP 1/2"	032 DU 21	25	40	

• **ONE HAND CONNECTION / EINKUPPELUNG MIT EINER HAND** •

For optional orders please add the symbol OH end of the order no.
Bei Bestellungen Kennbuchstabe OH hinzufügen



For only single shut-off sockets
Nur für den einseitig absperrende Kupplungen