



SERIE 051

PNEUMATIC COUPLINGS PNEUMATISCHE KUPPLUNGEN



SUPER FLOW LINE **SUPER DURCHFLUSS**

Interchangeability - Kompatibilität
RECTUS 51, WALTER SP 006, SG 006

Temperature Range - Temperaturbereich
-20°C +100°C (-4°F +212°F)

Working Pressure - Betriebsdruck
0 - 35 bar (0 - 508 PSI)



Flow capacity - Nennweite
NW - 6

Option - Optionen
F - Straight through flow - ungehinderter Durchfluss
K - Chrome plated - verchromt
V - Viton Seal - Viton Dichtung
Z - Zinc Plated - verzinkt

For optional orders please add the symbol of your option end of the order no.
Bei Optionsbestellungen Kennbuchstabe bitte hinzufügen (Beispiel: 051 EG 13-K-V)


Material - Material

- Coupler Body - Kupplungsgrundkörper: Steel Nickel Plated - Stahl vernickelt
- Back Part - Hinterteil : Brass Nickel Plated - Messing vernickelt
- Sleeve - Hülse : Steel Nickel Plated - Stahl vernickelt
- Valve - Ventil : Brass - Messing
- Springs - Federn : Stainless Steel - Edelstahl
- Locking O-Ring - Sprengling : Stainless Steel - Edelstahl
- Pins - Stifte : Stainless Steel -Edelstahl
- Seals - Dichtungen : Nitrile (Ni) - NBR (Ni)
- Plug - Nippel : Steel Hardened Nickel Plated - Stahl gehärtet vernickelt




**Couplers and Plugs
Kupplungen und Nippel**


Connection Anschlüsse	Order No Bestellnr.	SW	L	ØD
--------------------------	------------------------	----	---	----



BSP 1/4"	051 EG 13	21	62	22
BSP 3/8"	051 EG 17	21	62	22
BSP 1/2"	051 EG 21	22	65	22




BSP 1/4"	051 DG 13	21	64	22
BSP 3/8"	051 DG 17	21	64	22
BSP 1/2"	051 DG 21	24	65	22




6 mm - 1/4"	051 HG 06	21	76	22
9 mm - 5/14"	051 HG 09	21	76	22
11 mm - 7/16"	051 HG 11	21	76	22
13 mm - 1/2"	051 HG 13	21	76	22



6 mm - 1/4"	051 HU 06		44	
9 mm - 5/14"	051 HU 09		44	
11 mm - 7/16"	051 HU 11		46	
13 mm - 1/2"	051 HU 13		46	



BSP 1/8"	051 EU 10	14	33	
BSP 1/4"	051 EU 13	17	35	
BSP 3/8"	051 EU 17	19	36	
BSP 1/2"	051 EU 21	22	39	



BSP 1/8"	051 DU 10	14	30	
BSP 1/4"	051 DU 13	17	34	
BSP 3/8"	051 DU 17	19	34	