

HYDRAULIC COUPLINGS
HYDRAULIK KUPPLUNGEN

SERIE 074F



AGRICULTURAL COUPLER **AGRAR-HYDRAULIK SERIE** FLAT-FACE




Couplers and Plugs
Kupplungen und Nippel

Connection Anschlüsse
ØT


Order No Bestellnr.

L LI ØD Max. Work Press Bar SW




Female Thread Coupler
Kupplung mit Innengewinde

M 18x1.5	074F DGBM 18	55	45	220	27
M 20x1.5	074F DGBM 20	55	45	220	27
3/8"	074F DGB 17	55	45	220	27
1/2"	074F DGB 21	55	45	220	27



Male Thread Plugs
Nippel mit Außengewinde

M 18x1.5	074F EUBM 18	51	23	220	32
M 20x1.5	074F EUBM 20	51	23	220	32
1/2"	074F EUB 21	43	15	220	32



Female Thread Plugs
Nippel mit Innengewinde

1/2"	074F DUB 21	51		220	32
------	-------------	----	--	-----	----

Interchangeability - Kompatibilität
PARKER 5676 serie Hansen - Gromelle Serie 9000

Temperature Range Temperaturbereich
-20°C +100°C (-4°F +212°F)

Working Pressure - Betriebsdruck
Max. 220 bar - 3300 PSI (max.)

Flow capacity - Nennweite
NW Ø8 mm.

Material - Material
Main parts made of Steel
Bichromated - Zing Plated
All Highly Stressed component
Are Hardened
Seals - Nitrile (Ni) - NBR (Ni)
Buck-Up Ring - PTFE

